

Xerox® WorkCentre® 3655i Multifunction Printer

The WorkCentre 3655i Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to **www.connectkey.com**.





| System Specifications | WorkCentre 3655i/S | WorkCentre 3655i/X | |
|--|---|---|--|
| Speed | Up to 47 ppm 8.5 x 11 in. Up to 45 ppm A4 / 210 x 297 mm Up to 36 ppm 8.5 x 14 in. / 216 x 356 mm | | |
| Monthly Duty Cycle ¹ | Up to 150,000 pages | | |
| Recommended Average Monthly Print Volume ² | Up to 15,000 pages | | |
| Hard Drive / Processor / Memory | Minimum 250 GB / 1 GHz Dual-core / 2 GB | | |
| Connectivity | 10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Wi-Fi Direct with | Optional Xerox® USB Wireless Adapter | |
| Controller Features | Unified Address Book, Remote Control Panel, Online Support (accessed from the | user interface and print driver), Configuration Cloning | |
| Copy and Print | | | |
| Copy and Print Resolution | Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi | | |
| First-print-out Time | As fast as 8 seconds | | |
| First-copy-out Time | As fast as 12 seconds | | |
| Page Description Languages | Adobe® PostScript® 3™, Adobe® PDF version 1.7, PCL® 5c / PCL 6, XML Paper Specification (XPS®) | | |
| Print Features | Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Store and Recall Driver Settings, Bidirectional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs | | |
| Mobile Printing and Apps | Standard: Apple® AirPrint™, Mopria® Certified, QR Code App, Xerox® App Gallery App, @PrintByXerox App; Free Download: Xerox® Print Service Plug-in for Android, Mopria® Print Service Plug-in for Android, Mopria® Print Service Plug-in for Android™, Xerox® Mobile Link App; Optional: Xerox® Mobile Print, Xerox® Mobile Print Cloud, Xerox® Easy Translator Service | | |
| Scan | | | |
| Standard Features | Destinations : Scan to Mailbox, Scan to USB, Scan to Email, Scan to Network; File Formats : PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features : Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-page PDF/XPS/TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A | | |
| Optional Features | ConnectKey® for DocuShare®, Xerox® Scan to PC Desktop® SE and Professional, numerous solutions available through various Xerox Alliance Partners | | |
| Fax | | | |
| Standard Features | Internet Fax, Network Server Fax Enablement | Walk-up Fax³, LAN Fax, Internet Fax (includes LAN Fax (Fax forward to Email or SMB)), Network Server Fax Enablement | |
| Security | | | |
| Standard Features | McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, AES 256-bit Encryption (FIPS 140-2 compliant), SHA-256 Hash Message Authentication, Common Criteria Certification (ISO 15408) (undergoing evaluation), Encrypted Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, TLS, SNMPv3, Audit Log, Access Controls, User Permissions | | |
| Optional Features | McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET), Xerox® PrintSafe Software | | |
| Accounting | | | |
| Standard Features | Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement | | |
| Optional Features | Equitrac Express®, Equitrac Office®, YSoft® SafeQ®, other network accounting solutions available | | |

| Device Specifications | | | | |
|---------------------------------------|--|--|---|-----------------------------|
| Control Panel Languages | US English, International English, Inte Danish, Finnish, Turkish, Greek, Russia | | ternational Spanish, Dutch, Brazilian Portu | uguese, Swedish, Norwegian, |
| Accessories | Duriisti, Firiffisti, Turkisti, Greek, Kussic | in, czecn, rollsh, Hangahan, Alabic | | |
| Optional Accessories | 550-sheet Feeder Stand Smart Card Enablement Kit Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit | | | |
| Electrical Requirements | | | | |
| North America | Voltage : 110-127 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 11 A | | | |
| Europe | Voltage : 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 % , 6 A | | | |
| Power Consumption | | | | |
| Running (Average)" | 110V: 525.1 watts 220V: 523.0 watts | | | |
| Standby Mode ⁴ | 110V: 81.7 watts 220V: 80.5 watts | | | |
| Low Power Mode ⁴ | 110V: 2.8 watts 220V: 3.0 watts | | | |
| Auto off / Sleep Mode ⁴ | 110V: 0.4 watts 220V: 0.6 watts | | | |
| Warm up | Time from power off to when service | s are displayed: As fast as 165 second | ds | |
| Low Power Recovery ⁴ | <11 seconds | | | |
| Operating Environment | | | | |
| Required Temperature Range | 41° to 90° F (5° to 32° C) | | | |
| Required Relative Humidity | 15% to 85% | | | |
| Sound Power Levels | Operating 7.27 B(A), Standby: 4.8 B(A) | 4) | | |
| Sound Pressure Levels | Operating: 55.9 dB(A), Standby: 31.9 | dB(A) | | |
| Dimensions and Weight (Unpackaged) | Width | Depth | Height | Weight |
| WorkCentre 3655i/S | 22.0 in. / 560 mm | 21.3in. / 541 mm | 22.7 in. / 577 mm | 56 lbs. / 25.4 kg |
| WorkCentre 3655i/X | 22.0 in. / 560 mm | 21.3in. / 541 mm | 22.7 in. / 577 mm | 58 lbs. / 26.3 kg |
| 550-sheet Feeder | 19.5 in. / 495 mm | 18.5 in. / 469 mm | 3.8 in. / 96.3 mm | 9.3 lbs. / 4.2 kg |
| Stand | 29 in. / 737 mm | 27.5 in. / 699 mm | 13.1 in. / 332 mm | 28.4 lbs. / 12.9 kg |
| Dimensions and Weight (Packaged) | Width | Depth | Height | Weight |
| WorkCentre 3655i/S | 25.7 in. / 653 mm | 26.5 in. / 674 mm | 28.5 in. / 723 mm | 68.8 lbs. / 31.2 kg |
| WorkCentre 3655i/X | 25.7 in. / 653 mm | 26.5 in. / 674 mm | 28.5 in. / 723 mm | 70.8 lbs. / 32.1 kg |
| 550-sheet Feeder | 22.6 in. / 575 mm | 23.4 in. / 601 mm | 9.5 in. / 241 mm | 12.8 lbs. / 5.8 kg |
| Stand Certifications | 22 in. / 560 mm | 20.9 in. / 530 mm | 10.6 in. / 270 mm | 36.6 lbs. / 16.6 kg |
| | FCC Part 15, Class A FCC Part 68 CE Mark applicable to Directives 200t UL 60950-1/CSA 60950-1-07, 2nd Ed EAC ROHS Directive 2011/65/EU WEEE Directive 2012/19/EU Citrix Cerner Common Criteria (IEEE 2600.2 stand Apple® AirPrint™ 1.4 Certification Mopria® Certified Wi-Fi Direct Certification Blue Angel ECOLOGO® (undergoing evaluation) EPEAT (United States) ENERGY STAR® qualified To view the latest list of certifications | dition ard) (undergoing evaluation) | | |

| Deplets Automatic Deciment Feeder (DADF) | Paper Handling | | | |
|--|---------------------------------------|--|--|--|
| Capacity | | | | |
| Speed | - | | | |
| Titles Kend whele Up to 24 minutes (pm) letter 33 (pm A4 (complex) Up to 29 minutes 72 (pm A4 (complex) Up to 29 minutes 72 (pm A4 (complex) Up to 29 minutes 72 (pm A4 (complex) Up to 40 pm Interes 71 (pm A4 (complex) Up to 40 pm Interes 71 (pm A4 (complex) Up to 40 pm Interes 71 (pm A4 (complex) Up to 40 pm Interes 71 (pm A4 (complex) Up to 40 pm Interes 71 (pm A4 (complex) Up to 40 pm Interes 71 (pm A4 (complex) Up to 40 pm Interes 71 (pm A4 (complex) Up to 40 pm Interes 71 (pm A4 (complex) Up to 40 A4 (complex) Up to 50 | | OU SHEELS | | |
| Prope Sizes Sensed | Black and white Colour | Up to 25 ipm Letter / 24 ipm A4 (duplex) Up to 29 ipm Letter / 28 ipm A4 (simplex) | | |
| Simplane 1 8 lb. bond to 3 2 lb. bond / 60 gmm to 125 gmm Simplane 1 9 lb. bond to 3 2 lb. bond / 60 gmm to 125 gmm Simplane 1 9 lb. bond to 6 3 lb. bond / 60 gmm to 125 gmm Sizes | Paper Sizes Sensed | | | |
| Spoess Tray 150 sheets | Weights | | | |
| Capacity' 150 sheets Castom sees 3 x 5 in 16 8.5 x 14 in 1 / 76.2 x 127 mm to 216 x 356 mm | Bypass Tray | | | |
| Custom Sizes Custom Sizes 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356 mm | | 150 sheets | | |
| Poin | Sizes | Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356 mm | | |
| Plan | | | | |
| Capacity* \$50 sheets Sizes Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Lobels Pre-printed Custom Custom Capacity* \$50 sheets each Sizes Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Types Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Lobels Pre-printed Custom Total Capacity 2 2,350 sheets each Device Standard Capacity 3 700 sheets Device Total Capacity 2 2,350 sheets Poevice Total Capacity Up to 250 sheets, automatic two sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Types | Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Labels Pre-printed Envelopes | | |
| Capacity* \$50 sheets Sizes Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Lobels Pre-printed Custom Custom Capacity* \$50 sheets each Sizes Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Types Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Lobels Pre-printed Custom Total Capacity 2 2,350 sheets each Device Standard Capacity 3 700 sheets Device Total Capacity 2 2,350 sheets Poevice Total Capacity Up to 250 sheets, automatic two sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Trays 1 | | | |
| Sizes Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Lobels Pre-printed Custom Up to 3 Additional Trays Capacity* 550 sheets each 16 lb. bond to 80 lb. cover / 60 to 216 gsm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Types Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Types Plain Punched Lightweight Card stock, Card stock Recycled Bond Lobels Pre-printed Custom Total Capacity 70 sheets 70 she | Capacity ⁵ | 550 sheets | | |
| Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Types Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Lobels Pre-printed Custom Up to 3 Additional Trays Capacity* 550 sheets each Sizes Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Types Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Lobels Pre-printed Custom Lobels Pre-printed Custom Total Capacity 700 sheets Device Standard Capacity* 700 sheets Pager Output Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/K), not available on WorkCentre 3655i/K) | Sizes | Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm | | |
| Plain | Weights | | | |
| Capacity 550 sheets each Sizes Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Labels Pre-printed Custom Total Capacity Device Standard Capacity 700 sheets Device Total Capacitys 2,350 sheets Paper Output Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X), not available on WorkCentre 3655i/S) | Types | Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Labels Pre-printed | | |
| Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Labels Pre-printed Custom Total Capacity Device Standard Capacity ⁵ 700 sheets Device Total Capacity ⁵ 2,350 sheets Paper Output Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Up to 3 Additional Trays | | | |
| Weights 16 lb. bond to 80 lb. cover / 60 to 216 gsm Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Labels Pre-printed Custom Total Capacity Device Standard Capacitys 700 sheets Device Total Capacitys 2,350 sheets Paper Output Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/S, not available on WorkCentre 3655i/S) | Capacity ⁵ | 550 sheets each | | |
| Plain Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Labels Pre-printed Custom Total Capacity Device Standard Capacitys 700 sheets Device Total Capacitys 2,350 sheets Paper Output Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Sizes | Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm | | |
| Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Labels Pre-printed Custom Total Capacity Device Standard Capacitys 700 sheets Device Total Capacitys 2,350 sheets Paper Output Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Weights | 16 lb. bond to 80 lb. cover / 60 to 216 gsm | | |
| Device Standard Capacitys 700 sheets Device Total Capacitys 2,350 sheets Paper Output Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Types | Punched Letterhead Lightweight Card stock, Card stock Recycled Bond Labels Pre-printed | | |
| Device Total Capacity ⁵ 2,350 sheets Paper Output Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Total Capacity | | | |
| Paper Output Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Device Standard Capacity ⁵ | 700 sheets | | |
| Capacity Up to 250 sheets, automatic two-sided Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Device Total Capacity ⁵ | 2,350 sheets | | |
| Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Paper Output | | | |
| Offline Convenience Stapler (Standard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S) | Capacity | Up to 250 sheets, automatic two-sided | | |
| | Offline Convenience Stapler (Sta | | | |
| | Capacity ⁵ | | | |

| Сору | |
|--------------------------|---|
| Speed (cpm) | Up to 47 cpm 8.5 x 11 in. |
| Speed (cpiii) | Up to 45 cpm A4 / 210 x 297 mm |
| | Up to 36 cpm 8.5 x 14 in. / 216 x 356 mm |
| First-copy-out Time | As fast as 12 seconds |
| Sides (input:output) | 1-1, 1-2, 2-2, 2-1 |
| Quantity | 1 to 9,999 |
| Resolution (max.) | Up to 600 x 600 dpi |
| Reduction / Enlargement | Variable zoom from 25% to 400% in 1% increments |
| Concurrency | Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan) |
| Copy Features | Annotation and Bates** stamping Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling |
| Xerox® Copier Assistant® | Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com. |
| Print | |
| First-print-out Time | As fast as 8 seconds |
| Print Resolution | Up to 1200 x 1200 dpi |
| Print Features | Application Defaults Banner Sheet Enable / Disable Bidirectional Real-time Status Booklet Printing Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Standard and High Resolution) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark N-up (up to 16 pages per sheet) Booklet layout Finishing Fit to new paper size Hold All Jobs Paper Selection by Attribute Print Around Proof Print Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox* Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default) |
| Print from USB | Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL |

| Operating Systems | Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 SP2 R2 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.8, 10.9, 10.10, 10.11 Linux® Redhat® Fedora® Core 20 x86 Ubuntu® 14.04 x64 openSUSE® 13.1 x64 |
|---|--|
| Network Protocols | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® / AirPrint™ IPv6 Secure FTP Most protocols not in use can be disabled |
| Administrative Protocols | DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP |
| Fonts | PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts |
| Xerox [®] Mobile Express Driver [®] | Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. |
| Xerox® Global Print Driver® | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. |
| Xerox® Pull Print Driver | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others. |
| Print Solutions | |
| Xerox® Mobile Print Cloud (Optional) | Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it. |
| Xerox® Mobile Print Solution (Optional) | Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment. |
| Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store) | The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store. |
| Xerox® Mobile Link App (Free at Google Play Store and Apple® App Store) | The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer. |
| Unified Address Book for Fax, Inte | ernet Fax, Email and Scan to |
| Features | Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of fax numbers, emails, etc. |
| Scan | |
| Concurrency | Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs) |
| Speed Black and white Colour | Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (duplex) Up to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex) |
| Resolution | 72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (grayscale), 24-bit (colour) |
| Maximum Scan Area | Up to 8.5 x 14 in. / 216 x 356 mm |
| Scan Template Management | Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options |
| Network Protocols | sFTP, FTP, SMB, NetWare, HTTP, HTTPS |
| | |

| File Compression | Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Encrypted / Password Protected PDF (Network Scan Templates only) Linearised PDF, PDF/A |
|--|--|
| Document Management Fields (Meta Data) | Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customised fields viewed on user interface for variable data input |
| Scan Features | Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression TWAIN Support, WIA 2.0 Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10) |
| Scan to Email (Standard) | |
| Scan Features | Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self |
| Directory Access | Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) |
| Scan to (Standard) | |
| Features | Scan to USB Scan to Network Folder (uses Unified Address Book entries) |
| Network Scanning – Software Sol | utions |
| Xerox® Scan to PC Desktop® Professional (Optional) | A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: • PaperPort Professional image viewing and file management software — Complete PDF functionality — Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) — Professional OCR software for digital archiving and document conversion • Image Retriever — provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability |
| Xerox [®] ConnectKey for DocuShare [®] (Optional) | Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer. |
| Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery) | Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer. |
| Security | |
| Features | Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP authentication Local Authentication (internal database) Smart Card authentication ·144k CAC / PIV Card Support (2048 bit certificate key) / .NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted / Password Protected PDF (when using Email and Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite / Securely delete jobs using approved algorithms On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorisation SA access based on network credentials Authorisation per user per service User Permissions required to access Print and Print Features reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration, Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 (undergoing evaluation) |
| Xerox® PrintSafe Software | This authentication software integrates with trusted industry cards and readers and provides PIN access to nearly any printer in a customer's secured print environment. It works with both Xerox® devices and devices from other vendors. This software is open to work with a variety of industry standard secure readers and cards. |

| Fax | |
|--|--|
| Walk-up Fax³, LAN Fax, Internet Fa WorkCentre 3655i/X only) | ıx (includes LAN Fax (Fax forward to Email or SMB)), Network Server Fax Enablement (Walk-up Fax and LAN Fax available on |
| Fax Speed | Up to 33.6 Kbps (analog) |
| Memory | Uses device memory |
| Resolution | Up to 600 x 600 dpi (Super Fine) resolution Up to 200 x 200 dpi (Fine) resolution Up to 200 x 100 dpi (Standard) resolution |
| Compression | MH, MR, MMR, JBIG |
| Fax Features | Duplex Scanning Reports Auto Redial Auto Reduction Cover Page Delayed Send Fax Forward to Email Memory Receive Polling Secure Fax Speed Dials (up to 200 individual, 100 group) |
| Device Management | |
| Management Support | SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2 |
| Xerox® CentreWare® Web | A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher. • CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView® |
| Novell NDPS/NEPS | Server gateway application: centralised management tool. |
| Xerox® Device Manager | Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities |
| Xerox® Device Types for SAP Environment | Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/software-solutions |
| Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional) | Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions |
| Xerox® Barcode Pro PS (optional) | Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions |
| CentreWare Internet Services – Int | tegrated Web Pages Provided by the Device |
| Device Status | Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel |
| Job Submission | Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint) |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device |
| Browsers | Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12 |
| Support | Install print / scan drivers and online support available via web page |
| Languages Supported | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic |

Xerox® WorkCentre® 3655i

| Remote Print Services | | | |
|---|--|--|-------------------------------------|
| Automatic Meter Reading (AMR) | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. | | |
| Automatic Supplies Replacement (ASR) | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries). | | |
| Accounting | | | |
| Xerox® Standard Accounting (Stan | dard) | | |
| Tracking | Copy, Print, Fax, Scan and Email usage | | |
| Accounting | Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department) | | |
| Features | Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file. | | |
| Accounting Options – Network Acc | counting (Allows central server to manage all accounting) | | |
| | Comprehensive management and enterprise scale tracking and reporting o Numerous solutions are available through Xerox Alliance Partners. For detai Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third party server enabling lar Accept Authentication Login at control panel and pass to third party Netwo Interface with third party accounting terminal for accounting user interface | ls visit www.xerox.com ger databases of users and according Account | |
| What Comes in the Box | | | |
| | WorkCentre 3655i Multifunction Printer Toner Cartridge (6,100 page capacity ⁶) Drum Cartridge (68,000 pages ⁷) Quick Installation Guide, Product Information Guide, Driver CD, Documentation Power Cable Fax Cord (WorkCentre 3655i/X) | CD (User Manual, System Admin (| Guide) |
| Supplies and Accessories | Description | Quantity | Part Number |
| Supplies | Standard Capacity Toner Cartridge High Capacity Toner Cartridge Extra-high Capacity Toner Cartridge | 6,100 pages ⁶ 14,400 pages ⁶ 25,900 pages ⁶ | 106R02737 106R02739 106R02741 |
| | Drum Cartridge | 68,000 pages ⁷ | 113R00773 |
| | Staple Cartridge | 3,000 staples | 108R00823 |
| Accessories | 550-sheet Feeder (Adjustable up to A4 / legal) | - | 097S04625 |
| | Stand (Adds storage capacity for supplies, device stability, mobility and 13.1 in. of height) | | 497K14670 |
| | Wireless Networking Adapter | - | 497K11500 |
| | McAfee Integrity Kit | - | 320S00665 |
| | | | |

 $^{^{\}mbox{\scriptsize 1}}$ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

Build and configure your own Xerox® WorkCentre 3655i Multifunction Printer at www.buildyourownxerox.com/connectkey.

For more information, visit us at www.xerox.com/office



² Expected regular monthly throughput.

³ Requires analog phone line.

⁴ Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

 $^{^{\}rm 5}$ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared Yield Drums based on an average job size of 3 pages A4/letter size. Drum yield will vary based on job run length, media type, size, weight, orientation and usage patterns.